

HATHORN CAMERA REELS

STANDARD



Get A Quote

PROUDLY DESIGNED AND MANUFACTURED IN NORTH AMERICA



For use with
Hathorn
Command
Modules



Self-Levelling
Camera Heads



200 ft to 500
ft of Push Rod



512Hz or
640Hz High
Power Sonde



Industry-Leading
Warranty

Hathorn® camera reels are designed to work with any Hathorn control module, past present or future. These rugged and durable camera reels come fitted with your choice of Hathorn self-levelling camera heads, all equipped with super-bright, cool running LEDs for optimal picture quality. Butt-welded steel frame construction, stainless steel camera heads and your choice of cable size allow you to push further than ever before and remain in the field longer with Hathorn's legendary reliability.

Hathorn camera reels are trusted by plumbers, municipalities, general contractors, home inspectors, petrochemical companies, and mining engineers to deliver a clear, recordable video inspection every time the camera is used. Designed and manufactured in North America, with a full one-year warranty.

HATHORN CAMERA REELS

STANDARD

PROUDLY DESIGNED AND MANUFACTURED IN NORTH AMERICA



Specifications

Display

Size & Type Compatible with all Hathorn control modules. H12+ recommended for best picture and options

Features

Sonde Frequency High power 512Hz or 640Hz (available only with H12+ controller)

Push Rod HDPE push rod with coax core - multiple lengths and thicknesses

Weight & Dimensions

Weight See specific item in list to the right
Dimensions (L x W x H) See specific item in list to the right

Environmental

Water Resistance - Camera & Rod IP67 to 60psi
Water Resistance - Battery Cradle IP65
Water Resistance - Reel Hub IP64
Operating Temperature 14°F to 122°F (-10°C to 50°C)
Storage Temperature -4°F to 140°F (-20°C to 60°C)

Extra Large		Camera Head	Self Levelling	Rod Length	Rod Size	Min. 90° Elbow	Weight	Max Pipe	Dimensions
Catalog #									
XLR-5568-SL	1.68"	✓	500 ft.	5/8"	3"	90lbs.	12"	33" x 29" x 16"	
XLR-5168-SL	1.68"	✓	500 ft.	1/2"	3"	75lbs.	12"	33" x 29" x 16"	

Large		Camera Head	Self Levelling	Rod Length	Rod Size	Min. 90° Elbow	Weight	Max Pipe	Dimensions
Catalog #									
LR-3168-SL	1.68"	✓	300 ft.	1/2"	3"	55 lbs.	12"	33" x 29" x 16"	
LR-2168-SL	1.68"	✓	200 ft.	1/2"	3"	45 lbs.	12"	33" x 29" x 16"	
LR-4143-SL	1.43"	✓	400 ft.	1/2"	3"	65 lbs.	10"	33" x 29" x 16"	
LR-3143-SL	1.43"	✓	300 ft.	1/2"	3"	55 lbs.	10"	33" x 29" x 16"	
LR-2143-SL	1.43"	✓	200 ft.	1/2"	3"	45 lbs.	10"	33" x 29" x 16"	

Mid		Camera Head	Self Levelling	Rod Length	Rod Size	Min. 90° Elbow	Weight	Max Pipe	Dimensions
Catalog #									
MR-2168-SL	1.68"	✓	200 ft.	1/2"	3"	42 lbs.	12"	29" x 18" x 15"	
MR-2143-SL	1.43"	✓	200 ft.	1/2"	3"	42 lbs.	10"	29" x 18" x 15"	
MR-2123-SL	1.23"	✓	200 ft.	400"	2"	42 lbs.	6"	29" x 18" x 15"	

Mini		Camera Head	Self Levelling	Rod Length	Rod Size	Min. 90° Elbow	Weight	Max Pipe	Dimensions
Catalog #									
MN-2123-SL	1.23"	✓	200 ft.	1/2"	2"	33 lbs.	6"	24" x 18" x 10"	
MN-2100	1.23"	X	200 ft.	3/8"	1.5"	33 lbs.	4"	24" x 18" x 10"	

*Straight View Cameras Available

