

HATHORN H2

CAMERA SYSTEM



Get A Quote

PROUDLY DESIGNED AND MANUFACTURED IN NORTH AMERICA



Self-Leveling
Camera Heads



Works with 18V
Milwaukee® or
Equivalent
Batteries



200 ft of
Push Rod



512Hz High
Power Sonde



Industry-Leading
Warranty

The Hathorn® H2 comes with a 7" shatter-resistant LCD monitor, 200 ft. of premium push rod and your choice of straight-view or self-leveling camera heads, all with cool running, super-bright LED lights. The H2 also includes an on-screen footage counter in feet and meters, as well as a 512Hz high power sonde control.

Being aimed at the budget conscious user who wants a robust, easy-to-use system, without paying for extra options, the H2 camera system does not have a recording option. The H2 is an entry level inspection camera offering the same rugged quality and portability of our more expensive models. All Hathorn products are compatible with 18V Milwaukee® batteries offering the H2 over 6 hours of runtime on a single charge.

Trusted by plumbers and contractors to deliver rugged dependability and portability. Designed and manufactured in North America, with a full one-year warranty.

HATHORN H2

CAMERA SYSTEM

PROUDLY DESIGNED AND MANUFACTURED IN NORTH AMERICA

Specifications

Display

Size & Type	7" (17.8cm) impact-resistant LCD
Resolution & Brightness	1024 x 600 pixels with 1,000 cd/m2

Recording, Storage & Features

Footage Counter	Feet or meters - resettable
Sonde Frequencies	High power 512Hz
Push Rod	200 ft. of HDPE push rod with coax core

Power

Battery (not incl.)	Only Milwaukee® M18 18V or equivalent
Battery Life	~6Hrs. using 3.0Ah
AC/DC Adapter	12V - 4.1A (included)

Weight & Dimensions

Weight without Battery	45lb (20.4Kg)
Dimensions (L x W x H)	19" x 15.5" x 29.5" (48cm x 39cm x 75cm)

Environmental

Water Resistance	IP65 when the lid is closed
Operating Temperature	14°F to 122°F (-10°C to 50°C)
Storage Temperature	-4°F to 140°F (-20°C to 60°C)



Catalog #	Camera Head	Self Levelling	Rod Length	Rod Size	Min. 90° Elbow	Max Pipe Well Lit
H2-2168-SL	1.68"	✓	200 ft	1/2"	3"	12"
H2-2143-SL	1.43"	✓	200 ft	1/2"	3"	10"
H2-2123-SL	1.23"	✓	200 ft	0.400"	2"	6"
H2-2100	1"	✗	200 ft	3/8"	1.5"	4"

